

HF3000C-UQA Series (RoHS 対応品)

三相三線式 480VAC

高減衰・大電流(低漏洩電流タイプ)



150A品 外観

UL1283 (file No.E102708)
EN60939-2 (file No.R50031225)

用途




IGBTインバータ、ACサーボ、NC制御機器など

仕様

Part No.	Rated Current	Weight	
HF3010C-UQA	10A	2.2kg	fig1
HF3020C-UQA	20A	2.8kg	
HF3030C-UQA	30A	3.3kg	
HF3040C-UQA	40A	4kg	
HF3050C-UQA	50A	4kg	
HF3060C-UQA	60A	4.5kg	fig2
HF3100C-UQA	100A	11kg	
HF3150C-UQA	150A	14kg	fig3
HF3200C-UQA	200A	20kg	fig4
HF3250C-UQA	250A	21kg	
HF3300C-UQA	300A	22kg	
HF3400C-UQA	400A	33kg	fig5
Rated Voltage	480VAC max		
Leakage Current	10mA max / 400VAC 50Hz By UL1283		
Ambient temp.	-20 up to 50 Deg.C		


fig.1 (10-60A)

Model Name	Size (mm)										
	A	B	C	D	E	F	G	H	J	K	L
HF3010C-UQA	186	171	156	136	98	84	73	95	φ4.5×6	M4	M4
HF3020C-UQA	236	221	206	184	105	90	76	122	φ5.5×7	M5	M5
HF3030C-UQA											
HF3040C-UQA	256	241	226	204	115	100	86	127	φ5.5×7	M5	M5
HF3050C-UQA											
HF3060C-UQA											




No	Item
1	Input terminal
2	Resin case
3	Label
4	Output terminal

fig.2 (80, 100A)




No.	名称 Item	規格 Standard
1	入力端子 Input Terminal	M8
2	金属ケース Metal case	
3	銘板 Label	
4	出力端子 Output Terminal	M8
5	接地端子 Earthing Terminal	M6

fig. 3 (150A)



No.	名称 Item	規格 Standard
1	入力端子 Input Terminal	M8
2	金属ケース Metal case	
3	銘板 Label	
4	出力端子 Output Terminal	M8
5	接地端子 Earthing Terminal	M6

fig. 4 (200, 250, 300A)



No	Item	Notes
①	Input terminal	M10
②	Metal case	
③	Label	
④	Output terminal	M10
⑤	Earthing terminal	M8







fig. 5 (400A)



No	Item	Notes
①	Input terminal	M12
②	Metal case	
③	Label	
④	Output terminal	M12
⑤	Earthing terminal	M10



減衰特性



回路図

