





RoHS10 Support



○規格 (Standard)
MIL-C-3608

○仕様 (Specification)

- 特性インピーダンス (Impedance) : 50 Ω
- 定格周波数 (Working Frequency Range) : DC~4GHz
- 電圧定在波比 (VSWR) : ≤ 1.25
- 挿入損失 (Insertion Loss) : N/AdB
- 定格電圧 (Voltage Rating) : 500V rms
- 耐電圧 (Proof Voltage) : 1500V rms
- 接触抵抗 (Contact Resistance) : 2mΩ max
- 絶縁抵抗 (Insulation Resistance) : ≥ 5000MΩ
- 適合保証回数 (Connector Life) : 500 times min

3	Contact	BRASS	GOLD
2	Dielectric	POM	WHITE
1	Body	ZNIC	NICKEL
No	DESCRIPTION	MATERIAL	FINISH

TOLERANCE DECIMALS .XX ±0.10 .X ±0.15 DIAMETER .X ±0.10				日本エレパーツ株式会社 NIHON ELEPARTS Co.,LTD	
Approved	Checked	Drawn			
 エレパーツ '20.06.01 池尾	 エレパーツ '20.06.01 大江	 エレパーツ '20.06.01 山崎	A4	N A M E	MCI-7039