

RoHS10 Support


REACH Support

CFSI Support

IP66 Waterproof after mating (Requires waterproof tube)

Reverse

○形状 (SHAPE)



○規格 (STANDARD)


MIL-C-39012

○仕様 (SPECIFICATION)

特性インピーダンス (Impedance): 50 Ω
 定格周波数 (Working Frequency Range): DC~6GHz
 電圧定在波比 (VSWR): ≤1.30 max at 6GHz
 挿入損失 (Insertion Loss): 0.04 dB max × √f GHz (f:Frequency)
 定格電圧 (Voltage Rating): 335 Vrms max
 耐電圧 (Proof Voltage): 750 Vrms max
 勘合保証回数 (Connector Life): 500 times min
 使用温度範囲 (Temperature range): -65°C~165°C
 推奨締め付けトルク (Recommended Torque) 0.8~1.1 Nm


○加工寸法 (ASSEMBLY)

RECOMMENDED CABLE STRIPPING DIMS



SOLDER CONTACT TO CABLE CENTER CONDUCTOR

RECOMMENDED CLIPPING TOOL SIZE



RECOMMENDED CRIMP HEIGHT 3.35±0.1

The tolerance in this area is ±0.10

7	GASKET	S. I. R	RED
6	R-ring	SUS304	NATURE
5	Ferrule	BRASS	NICKEL
4	Coupling Nut	SUS303	PASSIVATE
3	Contact	BeCU	GOLD
2	Dielectric	PTFE	NONE
1	Body	BRASS	GOLD
No	DESCRIPTION	MATERIAL	FINISH



TOLERANCE				日本エレパーツ株式会社 NIHON ELEPARTS Co.,LTD	
DECIMALS	.XX ±0.08	.X ±0.13			
DIAMETER	.X ±0.03			N A M E	RSMA-PS-1.5D
Approved	Checked	Drawn	Unit		
'22.02.01 山崎	'22.02.01 大江	'22.02.01 大江	mm		
			A4		2